



Instructions

Rear Upper Control Arm - Adjustable

Page 1 of 3

Contents - 1x upper control arm - on-car adjustable.

Application - Ford Mustang S197

2005-2010 vehicles - use **KTA204**

2011-2014 vehicles - use **KTA205**

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.



- Begin by removing rear seat base. Push seat 'backwards', then lift up.



- Loosen and remove 1x 24mm mounting bolt (don't discard).

N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.



Instructions

Rear Upper Control Arm - Adjustable

Continued - Page 2 of 3

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.



- Raise vehicle evenly and safely support.
Never rely on a Jack only



- Proceed to un-bolt original control arm, including mount bracket.

N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.



Instructions

Rear Upper Control Arm - Adjustable

Continued - Page 3 of 3

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.



- Proceed to assemble new supplied arm.

1. Confirm diff bracket orientation - welded support piece should face upwards.

2. Adjust control arm length as per original bracket length.

(note - **KTA204** suits 2005-2010
KTA205 suits 2011-2014 cars)



- Proceed to bolt to vehicle.

Re-use OE mount bolts for floor mount and diff mount.

Road-test and re-check all bolts.

Pinion angle and Instant Centre (for Anti-Squat) can now be fine tuned as per preference.

N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.