

PERRIN

PERFORMANCE

License Plate Delete

2013-05-28

Thank you for purchasing this PERRIN product for your car! Installation of this product should only be performed by persons experienced with installation of aftermarket performance parts and proper operation of high performance vehicles. If vehicle needs to be raised off the ground for installation, the installer must use proper jacks, jack-stands and/or a professional vehicle hoist for safety of the installer and to protect property. If the vehicle is lifted improperly, serious injury or death may occur! Please read through all instructions before performing any portion of installation. If you have any questions, please contact our tech department prior to starting installation. We can be reached in any of the following methods:

Email Tech@PERRINperformance.com
Instant Chat off the main page of www.PERRINperformance.com
Or simply call our tech team at 503-693-1702

SPECIAL NOTES:

- Installation of this part will vary from year to year and model to model. Included is hardware to install this on virtually any Subaru.
- Some states it is not legal to remove front plate from car. Please check with local law enforcement before installing.

Parts Included with the PERRIN License Plate Delete:

- (1) PERRIN License Plate Delete
- (2) OEM Plastic Plate Mounts
- (2) #14 x 3/4" Flat Head Screws
- (2) 1/4-20 x 3/4" Flat Head Screw
- (2) 1/4" SS Lock Washer
- (2) 1/4" SS Flat Washer

Installation of PERRIN License Plate Delete

1. Remove existing front license plate from car.
2. Decide which method to use to install to license plate delete.
 - a. If there is an existing plate installed on the front of car, remove and install PERRIN License Plate Delete using supplied stainless steel sheet metal screws. This will screw into the bumper plastic in most situations. **NOTE: Do not over tighten either style of screw as these are threading into plastic.**
 - b. If there is an existing plate installed on the front of car and you have a front mounted intercooler installed, remove plate and install PERRIN License Plate Delete using supplied nuts, bolts and washers. These are easier to use as you can reach behind the bumper to install hardware.
 - c. If your car has the OEM square holes where PERRIN License Plate Delete goes, locate (2) OEM plastic plate mounts and supplied #14 screws. Pre-Install screws 4 turns into OEM plastic plate mounts from the square side (not the "finger" side) to help create threads. Remove screws and install OEM plastic mounts into holes in bumper making sure round face is on outside of bumper. Install PERRIN plate delete to bumper and using #14 screws and OEM plate mounts. NOTE: As the screws are installed, the OEM plastic plate mounts will flare out into bumper grabbing square hole. If these want to twist in bumper, screw with less force, or remove and repeat above step to thread in screw.
3. After a few days of driving, check that screws are still tight to ensure plate doesn't fall off car.

Questions, Comments and Suggestions Contact: Tech@PERRINperformance.com
Visit Our Website for Instant Chat Options at www.PERRINperformance.com
Call Our Tech Team at 503-693-1702